




COMFORT UP 2 PLUS i-Size MANUAL



MODEL: COMFORT UP 2 PLUS / COMFORT UP 2 CLASSIC i-Size
ECE R129.04 v.1.0

ATTENTION! The product graphic is for illustrative purposes only!





1.0 Application

The child car seat has been designed, tested, and approved in accordance with the requirements of UN Regulation No. 129 concerning the approval of enhanced child restraint systems (UN/ECE R129/04).

The seat is intended for children with a height of 76 cm to 150 cm and is installed forward-facing.

The seat may be installed in the vehicle on seats indicated by the vehicle manufacturer in the vehicle manual. It is required to read the vehicle manufacturer's instruction manual.

Child height	Seat orientation	Seat installation	Child restraint
76 cm – 105 cm / ≤18kg		3-point safety belt 	internal harness 
100 cm – 150 cm		3-point safety belt 	3-point safety belt 
140 cm – 150 cm		3-point safety belt 	3-point safety belt 



2.0 Safety instructions

Please take a few minutes to read this manual to ensure proper safety for your child.



- DO NOT install the seat on vehicle seats facing rearward or sideways relative to the direction of travel.



- The seat may only be installed if the seat is equipped with a 3-point safety belt.
- If installing the seat on the front seat, the front airbag must be deactivated.



- It is recommended to install the seat only on the rear seats of the vehicle.



WARNINGS!

Please take a few minutes to read this manual to ensure proper safety for your child. Many easily avoidable injuries are caused by careless and improper use of the seat.

! The car seat is intended for installation only on vehicle seats facing forward. It must not be installed on vehicle seats/benches facing rearward or sideways relative to the direction of travel.

! If the car seat is installed on the front seat, the front airbag must be deactivated. It is recommended to install the seat only on the rear seats of the vehicle. Information regarding the suitability of a vehicle seat for use with a child seat can be found in the vehicle user manual.

! Ensure that the internal harness securing the child is properly adjusted to the child's body and is not twisted. For this reason, the child should not wear thick clothing under the harness.

! The lap belts must run as low as possible across the child's pelvis to ensure optimal protection in the event of an accident.

! The car seat must be replaced if it has been subjected to violent loads during a road accident.

! The car seat must not be used without the cover.

! It is recommended to keep this instruction manual for the entire period of use of the seat.

! Do not use replacement covers other than those recommended by the manufacturer, as they are an integral part of the seat's safety system.

! Do not use any attachment points other than those described in the manual and marked on the seat.

! DO NOT use any other attachment points than those described in the instruction manual and marked on the car seat.


! All rigid elements and plastic parts of the child seat must be positioned and installed so that, under normal vehicle operating conditions, they cannot become trapped by a moving seat or a vehicle door.

! Regularly check the technical condition of the seat, paying particular attention to attachment points, seams, and adjustment elements. Ensure that all mechanical components are fully functional. Never lubricate or oil any parts of the child seat.

! Discontinue use of the seat if any parts are damaged or have become loose.

- ! No modifications may be made to the car seat without approval from the appropriate homologation authority. Failure to install the seat in accordance with the manufacturer's instructions may endanger life and health.
- ! Protect the child seat from direct sunlight, as heated components may cause burns to your child. Protect both the child and the seat from sunlight.
- ! Never leave your child unattended in the seat.
- ! Ensure that luggage and other items are properly secured, especially on the rear shelf, as they may cause injury in the event of a collision.

- ! In the event of an emergency, it is important to quickly release the safety harness. This means that the harness release button is not fully secured—ensure that your child does not play with the harness.
- ! Set a good example for your child and always fasten your seat belt. An unbelted adult can also pose a danger to the child.
- ! Before every journey, make sure the car seat is correctly installed.
- ! The car seat must be secured even when not in use. An unsecured seat can cause injury to passengers even during sudden braking.
- ! In some vehicles with delicate upholstery, the use of child seats may leave marks and/or cause discoloration. To prevent this, a blanket, towel, or similar item can be placed under the car seat.




3.0 Securing the child and adjusting the backrest


The backrest of the car seat is adjustable, allowing it to be precisely fitted to the contour of the vehicle seat. It is important that the car seat lies flush against the surface of the vehicle seat.



Recline the backrest until it is in a position that fully contacts the vehicle seat.



IMPORTANT! To ensure the child's comfort, move the front seat as far forward as possible to provide sufficient legroom for the child.



3.1 Headrest height


1. Grasp the headrest height adjustment lever located at the back of the headrest and gently pull it upwards.
2. Adjust the headrest by selecting one of the 12 positions; once the height is set, release the adjustment lever.




IMPORTANT! Make sure the headrest is securely locked.



The headrest should fit the child's head properly, with the lower edge of the headrest positioned at the level of the child's shoulders.






The correct shoulder strap height is when the straps run horizontally just above the child's shoulders.




3.2 Securing the child with internal harness

1. Press the internal harness adjustment button while pulling the straps at the same time. Remember: do not pull on the shoulder pads.
2. Unfasten the harness.
3. Place the internal straps to the sides of the seat.
4. Place the child in the seat.



5. Adjust the headrest to the child's height.
6. Fasten the harness.
7. Tighten and adjust the internal harness to the child by pulling the adjustment strap.



3.3 Tightening internal harness

1. Remove slack from the lap section of the internal harness by pulling the shoulder straps upwards.
2. Pull the adjustment strap until the harness lies flat against the child's body.




IMPORTANT! Make sure the internal harness is not twisted.



Ensure the harness is tightened so that there is no more than 1 cm of slack between the straps and the child's body.






3.4 Using the insert

The insert improves the child's comfort and provides additional support, especially for smaller children. It is recommended to use the insert until the child needs more space in the seat. At that point, the insert should be removed.


Installing the insert:

1. Press the internal harness adjustment button while pulling the straps at the same time. Remember: do not pull on the shoulder pads.
2. Unfasten the harness.
3. Place the internal straps to the sides of the seat.
4. Insert the inner cushion.




3.5 Storing internal harness.

1. Remove the shoulder strap pads according to the steps in section 5.0 (cover removal).
2. Remove the cover from the crotch buckle.
3. Loosen the internal harness as much as possible — press the harness adjustment button while pulling the straps.
4. Unfasten the snaps of the cover from the backrest and seat.
5. Thread the crotch buckle through the cover.
6. Lift the cover and foam and place the crotch buckle into the designated space in the seat.









7. Lift the cover and insert the harness fastening elements through the slots in the foam into the designated spaces.
8. Arrange the straps along the backrest.
9. Fasten the snaps of the cover.




3.6 Removing the backrest

1. Unfasten the plastic buckle located at the end of the internal harness adjustment strap.
2. Slide the strap out of the buckle.
3. Pull the strap from underneath the seat while simultaneously pressing the adjustment button.
4. Thread the strap through the opening at the back of the seat.
5. Fasten the plastic buckle back onto the harness adjustment strap.
6. Remove the metal buckles of the internal harness located under the seat.



7. Slide the straps out of the metal buckles.
8. Pull the straps through the seat and remove the harness fastening elements.
9. Install the metal buckles under the seat until you hear a click.
10. Push the backrest until you hear a click.
11. Detach the backrest from the seat.
12. Slightly remove the cover from the seat and thread the crotch buckle under the cover.
13. Store the buckle and the harness fastening elements inside the seat.




3.7 Installing the backrest

1. Place the backrest flat behind the seat.
2. Hook the lower part of the backrest (hooks) onto the seat.
3. Lift the backrest until it locks in the upright position. You will hear a characteristic click.
4. Unfasten the plastic buckle from the internal harness adjustment strap.
5. Thread the strap through the opening at the back of the seat. Make sure the strap is not twisted.



Note! When rotating the backrest, ensure that nothing is obstructing the connection point between the backrest and the seat.




6. Thread the strap through the opening in the seat while pressing the adjustment button.






IMPORTANT: The strap must pass through the adjustment mechanism.

7. Fasten the plastic buckle onto the harness adjustment strap.


8. Pull out the metal buckles from the seat.

9. Pull out the harness fastening elements from the seat.10. Attach connectors.





10. Attach the fastening elements onto the straps.
11. Lift the seat cover and thread the shoulder straps through the openings in the seat.
12. Attach the metal locking buckles to the straps.
13. Place the metal buckles of the internal harness into the designated spaces under the seat until you hear a click.
14. Pull the crotch buckle out of the seat and thread it through the opening in the cover.




4.0 Installation


WARNING! Do not use any booster under the car seat.

4.1 Children with a height of 76–105 cm – using the internal harness.

1. Place the car seat on the vehicle seat and push it as close as possible against the vehicle seat backrest.
2. Unfasten the snaps on the seat cover.
3. Route the shoulder belt through the green shoulder belt guide and under the internal harness.
4. Cover the vehicle belt with the lower part of the headrest cover.
5. Then route the lap belt through both lap belt guides and fasten the vehicle belt.
6. Make sure the vehicle belt is fully tightened. To remove slack, first tighten the lap section toward the buckle, then tighten the shoulder section.




7. Cover the vehicle belt with the seat cover.
8. Fasten the snaps on the seat cover.
9. Place the child in the car seat.
10. Adjust the headrest to the child's height.
11. Fasten the internal harness.
12. Adjust the internal harness to fit the child by pulling the harness adjustment strap.




4.2 Children with a height of 100–150 cm – using the vehicle’s 3-point safety belt.

1. Store the 5-point harness in the compartments in the seat according to section 3.5.
2. Place the car seat on the vehicle seat and push it as close as possible against the vehicle seat backrest.
3. Place the child in the car seat.
4. Adjust the headrest to the child’s height.
5. Route the shoulder belt through the green shoulder belt guide in the headrest.
6. Route the vehicle belt through both lap belt guides and fasten the belt. You will hear a characteristic “click”.
7. Make sure the vehicle belt is fully tightened. To remove slack, first tighten the lap section toward the buckle, then tighten the shoulder section.








4.3 Children with a height of 140–150 cm – using the vehicle's 3-point safety belt.

1. Remove the backrest according to section 3.6.
2. Place the car seat on the vehicle seat and push it as close as possible against the vehicle seat backrest.
3. Place the child in the car seat.
4. Pull out the shoulder belt and route it over the child's shoulder.
5. Route the vehicle belt through both lap belt guides.
6. Fasten the vehicle belt. You will hear a characteristic “click”.



5.0 Removing the cover

1. Raise the headrest to the highest position.
2. Unfasten the snaps located at the back of the headrest.
3. Remove the cover from the headrest.
4. Unfasten the shoulder strap pads.
5. Slide the straps of the shoulder pads off the hooks.
6. Unfasten the snaps located on the inner cover of the seat.



7. Loosen the harness as much as possible.
8. Unfasten the 4 snaps from the backrest.
9. Remove the cover from the backrest.
10. Push the backrest backwards to unlock it — when it unlocks, you will hear a characteristic click. Lay the backrest flat.
11. Remove the cover from the seat, starting from the rear.

5.1 Installing the cover

To reinstall the cover, simply reverse the above sequence of steps. Fit the cover to the attachment points on the car seat. Start by installing the cover on the seat base, then on the backrest, and finally on the headrest.



Make sure that the cover is correctly positioned over the lap belt guides.

6.0 Cleaning

Full warranty terms available at: WWW.KINDERKRAFT.COM

WARNING! Do not use the seat without a cover.

- Machine wash cover at max. 30°C with mild detergent. Air dry.
- Do not spin, tumble dry, or bleach.
- Follow label instructions.
- Do not expose to prolonged sunlight.
- Clean plastic parts with mild detergent.
- Do not use aggressive chemicals.
- Clean straps with damp cloth. Avoid soaking.



(AR) بضمان مصلحة عملائنا - نحن في خدمتكم! إذا كانت لديكم أي مشكلة مع المنتج الذي حصلتم عليه، فيجربى الاتصال بنا بالطريقة التي تفضلونها!

(CS) V zájmu péče o naše klienty - jsme rádi k dispozici! Pokud jste se setkali s nějakým problémem v souvislosti s obdržným výrobkem, kontaktujte nás způsobem, který vám nejvíce vyhovuje!

(DE) In Sorge für unsere Kunden - stehen wir gerne zu Ihrer Verfügung! Wenn Sie auf ein Problem mit dem erhaltenen Produkt treffen, treten Sie bitte mit uns in Kontakt in der bequemsten Weise für Sie!

(EN) In the interests of our Clients - we are at your disposal! If you have a problem with the product you received, contact us in the most convenient way for you!

(ES) ¡Por el bien de nuestros clientes, estamos a su disposición! ¡Si tiene cualquier problema con el producto recibido, póngase en contacto con nosotros de forma más cómoda para usted!

(FR) Dans l'intérêt de nos clients - nous sommes à votre disposition! Si vous avez un problème avec le produit que vous avez reçu, Contactez-nous de la manière la plus pratique pour vous!

(HU) Bármikor állunk az ügyfeleink rendelkezésére! Ha az átvett termékkel kapcsolatban valamilyen problémába ütközött, az Onnek legmegfelelőbb módon vegye fel velünk a kapcsolatot!

(IT) Prendersi cura dei nostri Clienti - siamo alla Vostra disposizione! Se hai incontrato un problema con il prodotto che hai ricevuto. Contattaci nel modo piu conveniente per te!

(NL) In het belang van onze klanten - staan wij ter beschikking! Als u een probleem met het ontvangen product tegenkomt, neemt contact met ons op via de manier die u het makkelijkste vindt!

(PL) W trosce o naszych Klientów - jesteśmy do dyspozycji! Jeśli napotkałeś problem dotyczący otrzymanego produktu, skontaktuj się z nami w najbardziej dogodny dla Ciebie sposób!

(PT) Para o conforto dos nossos Clientes - estamos sempre à sua disposição! Se tiver qualquer problema com o nosso produto, entre em contacto connosco de modo mais confortável para si!

(RO) In interesul clienților noștri - suntem la dispoziția dumneavoastră! Dacă aveți o problema cu produsul pe care l-ați primit, contactați-ne în modul cel mai convenabil pentru dvs.!

(RU) заботясь о наших клиентах, мы находимся в вашем распоряжении. Если вы столкнулись с проблемой, связанной с полученными продукто, свяжитесь с нами наиболее удобным для вас способом!

(SK) Náš zákazník je pre nás dôležitý - sme vám k dispozícii! Ak máte akýkoľvek problém súvisiaci s doručeným produktom, kontaktujte nás spôsobom, ktorý vám najviac vyhovuje!

(SV) I våra kunders intresse - vi står till ditt förfogande! Om du har problem med den produkt du fick, kontakta oss på det mest praktiska sättet för dig!

International contact:
help@kinderkraft.com
(0044) 7441 476675



kinderkraftofficial



kinderkraft



kinderkraftofficial

منتج/VÝROBCE/HERSTELLER/MANUFACTURER/FABRICANTE/FABRICANT/
GYARTÓ/FABBRICANTE/FABRIKANT/PRODUCENT/FABRICANTE/PRODUCĂTOR/
ПРОИЗВОДИТЕЛЬ/VÝROBCA/TILLVERKARE:

**4Kraft Sp. z o.o. ul. Tatrzńska 1/5
60-413 Poznań, Poland**